



83 139 0 83 139 5 83 139 2 83 139 1

| | | | |
|-------------------|-----------------|--|------------|
| 83 139 003 | | | |
| Standard | Low temperature | Double insulation to NFC 20030 standard class II | Flameproof |

| | | | |
|----------------------------|----------------------------|---------------------|---------------------|
| 6 | 6 | 6 | 6 |
| 11 | 11 | 11 | 11 |
| 3 | 3 | 3 | 3 |
| 0.6 | 0.6 | 0.6 | 0.6 |
| 4 | 4 | 4 | 4 |
| 10 | 10 | 10 | 10 |
| A = 8.8 B = 9.8 | A = 8.8 B = 9.8 | B = 9.8 | B = 9.8 |
| A = 7.7±0.4 B = 8.7±0.4 | A = 7.7±0.4 B = 8.7±0.4 | B = 8.7±0.4 | B = 8.7±0.4 |
| 0.35 ±0.1 | 0.35 ±0.1 | 0.35 ±0.1 | 0.35 ±0.1 |
| 0.25 | 0.25 | 0.25 | 0.25 |
| 0 +85 | -20 +85 | -20 +85 | -20 +85 |
| 10 ⁷ | 5 x 10 ⁶ | 5 x 10 ⁶ | 5 x 10 ⁶ |
| 0.3 x 2 | 0.3 x 2 | 0.3 x 2 | 0.3 x 2 |
| 37 | 37 | 45 | 37 |

| | | | |
|---|---|---|---|
| I | I | I | I |
|---|---|---|---|

| | | | |
|---|---|---|---|
| A | A | B | B |
|---|---|---|---|

| | | | |
|---|---|---|---|
| 4 flexible leads 0.75 mm ² length 0.50 m ext. Ø 2.3 mm | 4 flexible leads 0.75 mm ² length 0.50 m ext. Ø 2.3 mm | 3-lead cable 0.75 mm ² length 0.50 m ext. Ø 5.2 mm | 4 flexible leads 0.75 mm ² length 0.50 m ext. Ø 2.3 mm |
| S | S | - | S |
| D | D | - | D |
| G | G | - | G |

79 215 740 70 507 524 79 215 742 70 507 529

| | | | |
|------------------------|--------------------------|-----------------------------|-------------------------------|
| Flat 139 AX R29.7 mm** | Roller 139 EX R28.7 mm** | Flat 161 A R14.2 - R25.4 mm | Roller 161 E R13.6 - R24.1 mm |
| | | | |
| 1.5 | 1.5 | 2.6 | 1.7 |
| 0.2 | 0.2 | 0.35 | 0.2 |
| 1.5 | 1.5 | 0.7 | 1.25 |
| | | | 0.7 |
| | | | 1.7 |
| | | | 0.2 |
| | | | 1.2 |

79 218 651

Note : We recommend greasing the switch pushbutton lightly when fitting actuators.

Flat 161 F R22.3 mm Dummy roller 161 G R21.8

| | |
|-----|-----|
| | |
| 2 | 2 |
| 0.2 | 0.2 |
| 1.1 | 1.1 |

** Factory fitted

To order, specify :

| | | |
|--------------------------------|---|--|
| Standard products | 2 Part number plus connection type Example : 83 139 003 + 79 215 740 | 6 Actuators |
| Standard products, non stocked | 1 Type of microswitch Example : 83 139 5 - I - fixing A - Output connections D - 161A - R14.2 | 3 Function 4 Fixing 5 Connection 6 Actuators |